



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/731,950	12/10/2003	Woong-Kwon Kim	10125/4132	6763

7590 07/21/2010
Brinks Hofer Gilson & Lione
Post Office Box 10395
Chicago, IL 60610

EXAMINER

NGUYEN, HOAN C

ART UNIT	PAPER NUMBER
----------	--------------

2871

MAIL DATE	DELIVERY MODE
-----------	---------------

07/21/2010

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 10/731,950	Applicant(s) KIM ET AL.	
	Examiner HOAN C. NGUYEN	Art Unit 2871	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 03 February 2010.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1,2,6-13,18,19,22-35 and 46 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1,2,6-13,18,19,22-35 and 46 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Continued Examination Under 37 CFR 1.114


A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 02/03/2010 has been entered.

The independent claims 1, 18, 35 and 46 amended with the features:

(1) “...each color filter having a first top surface; a pixel electrode formed directly on a the first top surface in each pixel region, each pixel electrode contacting one of the drain electrodes through the drain contact hole, wherein a portion of the pixel electrode in the drain contact hole contacts the color filter defining the drain contact hole” and

(2) “...the light-shielding color filter patterns having a second top surface, wherein a thickness of the light-shielding color filter patterns is equal to or less than a thickness of the color filter, wherein the first and second top surfaces face the common electrode and have the same level.”

These amended features show in Figure 4 as following:



Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

*The secondary reference Midorikawa et al. (US 6281955 B1) disclose the plurality of pixel electrodes 30 formed directly on top surfaces of the plurality of color filters 24; **Midorikawa et al. fail to disclose “the first and second top surfaces face the common electrode and have the same level”**. However, the primary reference Yamamoto et al. (US6445432B2) discloses “the first and second top surfaces face the common electrode and have the same level”.*

1. Claims 1, 6-12, 18, 22-31, 35 and 46 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamamoto et al. (US6445432B2) in view of Midorikawa et al. (US 6281955 B1).


Yamamoto et al. teach (Figs. 2-4) a liquid crystal display device comprising:

Claims 1, 18, 35 and 46:

- a plurality of gate lines 3a formed on a first substrate along a transverse direction, each gate line including a gate electrode 3;
- a first insulating layer (gate insulating layer 4) formed on the first substrate to cover the gate lines and the gate electrodes;
- a plurality of data lines 6a formed on the first insulating layer along a longitudinal direction, the data lines defining a plurality of pixel regions with the gate lines and each including a source electrode 6;
- a thin film transistor formed at a crossing region of each of the gate and data lines, each thin film transistor including one of the gate electrodes, a semiconductor layer 5, one of the source electrodes, and a drain electrode;
- a color filter R over the first insulating layer in each pixel region, each color filter having one of red, green and blue colors R/G/B, the color filters having a plurality of drain contact holes exposing the drain electrodes 7;
each color filter having a first top surface;
- a pixel electrode 15 over a the first top surface in each pixel region, each pixel electrode contacting one of the drain electrodes through the drain contact hole, wherein a portion of the pixel electrode in the drain contact hole contacts inner side surfaces of the color filter defining the drain contact hole (see Figure 2 below);

Art Unit: 2871

- a common electrode on a second substrate 16, the common electrode facing the first substrate; and
- a liquid crystal layer 20 interposed between the common electrode and the pixel electrodes.
- plurality of transparent layers (color filters) including light shielding color filter patterns filling a space between the thin film transistor and the liquid crystal layer 20, the light shield color filter color patterns including at least two of red, green or blue resins, the light-shielding color filter patterns having a second top surface,



wherein

- a thickness of the light-shielding color filter patterns is equal to or less than a thickness of the color filter,

Art Unit: 2871

- the first and second top surfaces face the common electrode and have the same level of the surface of the flattening film 14.

Claims 1 and 22:

- the light-shielding color filter patterns are formed of the same material as the color filters.

Claims 6 and 23:

- a cell gap between the light-shielding color filter patterns and the common electrode is greater than zero.

Claims 7 and 24:

- the color filters are formed of a photosensitive resin through a photolithography process.

Claims 8 and 25:

- red, green and blue color filters are formed sequentially from the semiconductor layers towards the liquid crystal layer.

Claims 9 and 26:

- each of red, green and blue color filter patterns (at shielding regions) has a thickness smaller than each of red, green and blue color filters (at display regions).

Claims 10 and 27:

- each light-shielding color filter pattern has a red color filter pattern, a green color filter pattern and a blue color filter pattern.

Claims 11 and 28-29:

Art Unit: 2871

- a second insulating layer 9 between the thin film transistors 5 and the light-shielding patterns and between the first insulating layer 4 and the color filters, wherein the second insulating layer 9 covers the source electrodes 6, the drain electrodes 7 and the data lines and wherein the drain contact holes extend through the second insulating layer 9 wherein performing etching (Fig. 3C) an exposed portion of the second insulating layer such that the drain contact holes extend through the second insulating layer to expose a portion of each drain electrode.

Claims 12 and 30-31:

- a third insulating layer (a flattened film 14) between the color filters and the pixel electrodes, wherein the third insulating layer 14 covers the color filters and the light-shielding color filter patterns, wherein performing etching a portion of the third insulating layer corresponding to the drain contact holes such that the drain contact holes extend through the third insulating layer to expose a portion of each drain electrode.

However, Yamamoto et al. fail to disclose the plurality of pixel electrodes are formed directly on top surfaces of the plurality of color filters.

Midorikawa et al. (US 6281955 B1) teach (Fig. 1) the plurality of pixel electrodes 30 formed directly on top surfaces of the plurality of color filters 24 for obtaining high quality color images due to reducing the electrical coupling between color filter and TFT (col. 2 lines 45-48).

Art Unit: 2871

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to further modify a liquid crystal display device as Yamamoto et al. disclosed with the plurality of pixel electrodes formed directly on top surfaces of the plurality of color filters for obtaining high quality color images due to reducing the electrical coupling between color filter and TFT (col. 2 lines 45-48).

*In the following 103-rejection, both primary reference Yamamoto et al. (US6445432B2) and secondary reference **Yanai (US 6137552 A)** disclose "the first and second top surfaces face the common electrode and have the same level".*

2. Claims 1, 6-12, 18, 22-31, 35 and 46 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamamoto et al. (US6445432B2) in view of **Yanai (US 6137552 A)**.


Yamamoto et al. teach (Figs. 2-4) a liquid crystal display device comprising:

Claims 1, 18, 35 and 46:

- a plurality of gate lines 3a formed on a first substrate along a transverse direction, each gate line including a gate electrode 3;
- a first insulating layer (gate insulating layer 4) formed on the first substrate to cover the gate lines and the gate electrodes;
- a plurality of data lines 6a formed on the first insulating layer along a longitudinal direction, the data lines defining a plurality of pixel regions with the gate lines and each including a source electrode 6;

Art Unit: 2871

- a thin film transistor formed at a crossing region of each of the gate and data lines, each thin film transistor including one of the gate electrodes, a semiconductor layer 5, one of the source electrodes, and a drain electrode;
- a color filter R over the first insulating layer in each pixel region, each color filter having one of red, green and blue colors R/G/B, the color filters having a plurality of drain contact holes exposing the drain electrodes 7; each color filter having a first top surface;
- a pixel electrode 15 over a the first top surface in each pixel region, each pixel electrode contacting one of the drain electrodes through the drain contact hole, wherein a portion of the pixel electrode in the drain contact hole contacts inner side surfaces of the color filter defining the drain contact hole (see Figure 2 below);
- a common electrode on a second substrate 16, the common electrode facing the first substrate; and
- a liquid crystal layer 20 interposed between the common electrode and the pixel electrodes.
- plurality of transparent layers (color filters) including light shielding color filter patterns filling a space between the thin film transistor and the liquid crystal layer 20, the light shield color filter color patterns including at least two of red, green or blue resins, the light-shielding color filter patterns having a second top surface,



wherein

- a thickness of the light-shielding color filter patterns is equal to or less than a thickness of the color filter,
- the first and second top surfaces face the common electrode and have the same level of the surface of the flattening film 14.

Claims 1 and 22:

- the light-shielding color filter patterns are formed of the same material as the color filters.

Claims 6 and 23:

- a cell gap between the light-shielding color filter patterns and the common electrode is greater than zero.

Claims 7 and 24:

Art Unit: 2871

- the color filters are formed of a photosensitive resin through a photolithography process.

Claims 8 and 25:

- red, green and blue color filters are formed sequentially from the semiconductor layers towards the liquid crystal layer.

Claims 9 and 26:

- each of red, green and blue color filter patterns (at shielding regions) has a thickness smaller than each of red, green and blue color filters (at display regions).

Claims 10 and 27:

- each light-shielding color filter pattern has a red color filter pattern, a green color filter pattern and a blue color filter pattern.

Claims 11 and 28-29:

- a second insulating layer 9 between the thin film transistors 5 and the light-shielding patterns and between the first insulating layer 4 and the color filters, wherein the second insulating layer 9 covers the source electrodes 6, the drain electrodes 7 and the data lines and wherein the drain contact holes extend through the second insulating layer 9 wherein performing etching (Fig. 3C) an exposed portion of the second insulating layer such that the drain contact holes extend through the second insulating layer to expose a portion of each drain electrode.


Claims 12 and 30-31:


- a third insulating layer (a flattened film 14) between the color filters and the pixel electrodes, wherein the third insulating layer 14 covers the color filters and the light-shielding color filter patterns, wherein performing etching a portion of the third insulating layer corresponding to the drain contact holes such that the drain contact holes extend through the third insulating layer to expose a portion of each drain electrode.

However, Yamamoto et al. fail to disclose the plurality of pixel electrodes are formed directly on top surfaces of the plurality of color filters.

Yanai teach (Figs 3-4) the plurality of pixel electrodes 13 formed directly on top surfaces of the plurality of color filters 10 [wherein the first and second top surfaces face the common electrode and have the same level].

FIG. 3





3. Claims 2 and 19 rejected under 35 U.S.C. 103(a) as being unpatentable over Yamamoto et al. (US6445432B2) in view of **Midorikawa et al. (US 6281955 B1)** [or **Yanai (US 6137552 A)**] as applied to claims 1, 6-12, 18, 22-31 and 35 and in further view of Shin (US5825449A).

Yamamoto et al. fail to disclose a liquid crystal display device comprising the source and drain electrodes are formed on the ohmic contact layer and spaced apart from each other, and wherein each thin film transistor includes a channel on the active layer between the source and drain electrodes as cited in claims 2 and 19.

Shin teaches (Figs. 2-3) a liquid crystal display device comprising the source and drain electrodes are formed on the ohmic contact layer 5 and spaced apart from each other, and wherein each thin film transistor includes a channel on the active layer 4 between the source and drain electrodes for reducing the contact resistance between the active layer and the source/drain regions in the completed device as taught by Shin (col. 1 lines 43-48).

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to further modify a liquid crystal display device as Yamamoto et al. disclosed with the source and drain electrodes are formed on the ohmic contact layer and spaced apart from each other, and wherein each thin film transistor includes a channel on the active layer between the source and drain electrodes for reducing the contact resistance between the active layer and the source/drain regions in the completed device as taught by Shin (col. 1 lines 43-48).

Art Unit: 2871

4. Claims 13 and 32-34 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamamoto et al. (US6445432B2) in view of **Midorikawa et al. (US 6281955 B1)** [or **Yanai (US 6137552 A)**] as applied to claims 1, 6-12, 18, 22-31 and 35 and in further view of Song (US6307602B1).


Yamamoto et al. further disclose a liquid crystal display device comprising colors filters covering gate lines.

Yamamoto et al. fail to disclose a liquid crystal display device comprising a portion of each gate line acts as a first capacitor electrode and a second capacitor electrode on the first insulating layer over each portion of the gate line, wherein each second capacitor electrode and portion of the gate line constitute a storage capacitor with the first insulating layer interposed between the portion of the gate line and the second capacitor electrode. Each color filter includes a capacitor contact hole exposing one of the second capacitor electrodes and wherein the pixel electrodes contacts the second capacitor electrodes through the capacitor contact holes.

Song teaches (Fig. 4a-5f) a portion of each gate line acts as a first capacitor electrode and a second capacitor electrode 150 on the first insulating layer (gate insulating layer 111) over each portion of the gate line, wherein each second capacitor electrode 150 and portion of the gate line constitute a storage capacitor with the first insulating layer interposed between the portion of the gate line and the second capacitor electrode. The passivation layer 117 includes a capacitor contact hole exposing one of the second capacitor electrodes and

Art Unit: 2871

wherein the pixel electrodes contacts the second capacitor electrodes through the capacitor contact holes.



Combination of Yamamoto et al. and Song (Figs. 4-5 show storage electrodes covering gate lines) is obviously replaced the passivation layer by color filters for each pixel, which should includes capacitor contact hole exposing the second capacitor electrode, wherein the pixel electrode contact the second capacitor electrodes through the capacitor contact holes.

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to further modify a liquid crystal display device as Yamamoto et al. disclosed with a portion of each gate line acts as a first capacitor electrode and a second capacitor electrode 150 on the first insulating layer (gate insulating layer 111) over each portion of the gate line, wherein each second capacitor electrode 150 and portion of the gate line constitute a storage capacitor with the first insulating layer interposed between the portion of the gate line and the second capacitor electrode. The color filter

Art Unit: 2871

includes a capacitor contact hole exposing one of the second capacitor electrodes and wherein the pixel electrodes contacts the second capacitor electrodes through the capacitor contact holes for high display quality with preventing shorting between pixel electrodes as Song taught (col. 2 lines 25-34).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to HOAN C. NGUYEN whose telephone number is (571)272-2296. The examiner can normally be reached on MONDAY-THURSDAY:8:00AM-4:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Nelms can be reached on (571) 272-1787. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2871

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

HOAN C. NGUYEN
Primary Examiner
Art Unit 2871

Chn
/HOAN C. NGUYEN/
Primary Examiner, Art Unit 2871